

SAFETY DATA SHEET G-POLY 85 PART B

OTHER CALLS:

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

G-POLY 85 PART B HARDENER

CHEMICAL SPILL PRODUCT CODES: EMERGENCY PHONE: 800-255-3924 EPOXY 2U, LLC CHEMTEL PHONE:

MANUFACTURER: FLOOR COATING 2424 W 14TH STREET

FLOOR COATING

FAX PHONE: TEMPE AZ 85281 CHEMICAL NAME: CHEMICAL FAMILY: EPOXY 2U. LLC CHEMICAL FORMULA:

RDS IDENTIFICATION

Skin Sensitization: Category 1 GHS CLASSIFICATION: Flammable Liquids: Category 4

> Skin Irritation: Category 2 Eye Irritation: Category 2

PREPARED BY:

Clear Viscous Liquid PHYSICAL STATE:

Harmful if inhaled May cause allergy or asthma symptoms or breathing difficulties HAZARD STATEMENTS:

if inhaled May cause an allergic skin reaction May cause respiratory irritation

Do not handle until all safety precautions have been read and understood. Keep container PRECAUTIONARY STATEMENT(S):

tightly closed. Do not breathe dust/fume/gas/mist/vapors/spray. Wash skin thoroughly after handling, bDo not eat, drink or smoke when using this product. Contaminated work

clothing should not be allowed out of the workplace. Avoid release to the environment. Wear protective gloves/ protective clothing/ eye protection/ face protection.

IF SWALLOWED: rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin

with water/ shower.

IF INHALED: Remove victim to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if pres-

ent and easy to do. Continue rinsing. Call a POISON CENTER or doctor/ physician if you feel

unwell. Take off contaminated clothing and wash before reuse. If skin irritation or rash occurs: Get medical advice/ attention.

If eye irritation persists: Get medical advice/ attention. In case of fire: Use dry sand, dry

chemical or alcohol-resistant foam for extinction.

Store in a well-ventilated cool place. Keep container tightly closed. Store locked up.

Dispose of contents/ container to an approved waste disposal plant.

Combustible HAZARDS NOT OTHERWISE CLASSIFIED: Severe eye irritant

Severe respiratory irritant

May cause sensitization by skin contact



SAFETY DATA SHEET G-POLY 85 PART B

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

% BY WEIGHT Aspartic Ester 70-100

Trimethylpentanediol Diisobutyrate This product may contain additional ingredients that are classified as non-hazards or at a very

6846-50-0

small concentration that do not meet the regulatory concentration limits for disclosure. SECTION 4: FIRST AID MEASURES

Immediate and continuous irrigation with flowing water for at least 30 minutes is

required. Promptly seek medical attention.

Immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing, preferably under a safety shower. Seek medical attention immediately. Avoid prolonged or repeated contact to skin. Wash thoroughly after

handling.

Do not induce vomiting. Give large amounts of water or milk if available and

transport to medical facility.

INHALATION: Remove to fresh air if effect occurs. Consult medical personnel.

NOTES TO PHYSICIANS Corrosive. May cause stricture. lavage is performed, suggest endotracheal and/or esophagoscopic control. If burn is present, treat as any thermal burn, after

> decontamination. No specific antidote. Supportive care. Treatment based on judgment of the physician

EXTINGUISHING MEDIA: SPECIFIC HAZARDS ARISING FROM THE Foam, Powders, Carbon dioxide

Incomplete combustion may form carbon monoxide.

SUBSTANCES OF MIXTURE: May generate ammonia gas. May generate toxic nitrogen oxide gases. Burning produces noxious and toxic fumes. Downwind personnel must

be evacuated.

SPECIAL PROTECTIVE EQUIPMENT FOR Use personal protective equipment. FIREFIGHTERS: Wear self-contained breathing apparatus for firefighting if necessary.

> Do not allow run-off from firefighting to enter drains or water courses. Fire residues and contaminated fire extinguishing water must be disposed

of in accordance with local regulations

SECTION 6: ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS. PROTECTIVE EQUIPMENT.

AND EMERGENCY PRODUCERS

FURTHER INFORMATION:

Wear suitable protective clothing, gloves, and eye/face protection. Avoid breathing vapors/mist/gas. Ensure adequate ventilation. Remove all sources

of ignition. Evacuate personnel to safe areas. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas. For personal protection see section 8.

ENVIRONMENTAL PRECAUTIONS

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING-UP

Soak up with inert absorbent material and dispose of as hazardous waste. Keep in suitable, closed containers for disposal.

For disposal see section 13. ADDITIONAL ADVICE



SAFETY DATA SHEET G-POLY 85 PART B

SECTION 7: HANDLING AND STORAGE

Avoid contact with skin and eyes. Avoid inhalation of vapor or mist. Put on appropriate personal protective SAFE HANDLING: equipment before handling. Keep away from sources of ignition - No smoking. Take measures to prevent

the buildup of electrostatic charge.

CONDITIONS FOR Store in cool place. Keep container tightly closed in a dry and well-ventilated place. SAFE STORAGE: Containers which are opened must be carefully resealed and kept upright to prevent leakage.

HYGIENE PRACTICE: Eating, drinking and smoking should be prohibited in areas where this material is handled. Wash hands thoroughly after handling.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

CONTROL PARAMETERS Hexamethylene –di-isocyanate (CAS: 822-06-0) Threshold Limit Value: ACGIH 0.005ppm

National Institute for Occupational Safety and Health

Use process enclosures, local exhaust ventilation, or other engineering controls to keep worker exposure to air-

borne contaminants below recommended exposure limits. Wear appropriate personal protective equipment where such systems are not effective to perform satisfactorily and meets OSHA or other recognized standards. Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end

PERSONAL PROTECTION EQUIPMENT

PROTECTION:

of workday.

EYE/FACE PROTECTION: Tightly fitted safety goggles. Face shield (8-inch minimum). Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands after handling or

before eating, drinking, or smoking.

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the

supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario. Impervious clothing. Closed-toe shoe. Flame retardant antistatic protective clothing. The type of protective equipment must be selected according to the

concentration and amount of the dangerous substance at the specific workplace. Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multipur-

pose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Prevent further leakage or spillage if safe to do so. Do not allow product enter into sewers or waterways.

PHYSICAL STATE:	Viscous liquid	MELTING POINT / FREEZING POINT:	No data available	UPPER/LOWER FLAMMABILITY LIM	IT: No data available
ODOR:	Solvent	BOILING POINT/RANGE:	No data available	RELATIVE DENSITY:	1.175 g/cm3 at 77°F (25°C
ODOR THRESHOLD:	No data available	FLASH POINT:	No data available	PARTITION COEFFICIENT: N-OCTANG	DL/WATER No data available
COLOR:	Clear	EVAPORATION RATE:	No data available	AUTO-IGNITION TEMPERATURE:	No data available
PH:	No data available	VOC:	0 g/L	DECOMPOSITION TEMPERATURE:	No data available
VAPOR PRESSURE:	No data available	FLAMMABILITY (SOLID/GAS):	No data available	VISCOSITY:	50-150 CPS at 77°F (25°C
VAPOR DENSITY:	No data available	EXPLOSIVE PROPERTIES:	No data available	OXIDIZING PROPERTIES:	No data available
WATER SOLUBILITY:	<0.1 g/L				



SAFETY DATA SHEET G-POLY 85 PART B

SECTION 10: STABILITY AND REACTIVITY

CONTROL PARAMETERS No data available CHEMICAL STABILITY Stable under recommended storage conditions

POSSIBILITY OF HAZARDOUS REACTION No data available

CONDITIONS TO AVOID Heat, flames, sparks, and oxidizing agents

> Reactive metals (Sodium, Calcium, Zinc, etc.) Materials reactive with hydroxyl compounds Organic acids (acetic acid, citric acid, etc.) Mineral acids Sodium hypochlorite Product slowly corrodes copper, aluminum, zince, and galvanized surfaces. Reaction with peroxides may result in violent decomposition of peroxide

possibly creating an explosion Oxidizing agents

Nitric acid Ammonia Nitrogen oxides (NOx) Nitrogen oxide can react with water vapors to form corrosive DECOMPOSITION nitric acid Carbon monoxide Carbon dioxide (CO2) Aldehydes Flammable hydrocarbon fragments

PRODUCTS In the event of fire: see section 5

INFORMATION ON THE LIKELY ROUTES OF EXPOSURE

SKIN PROTECTION:

EYE CONTACT: Cause eve irritation SKIN CONTACT: Cause skin irritation INHALATION: No data available INGESTION: No data available SYMPTOMS RELATED TO PHYSICAL, CHEMICAL, AND TOXICOLOGICAL EFFECTS

EYE CONTACT: Cause eye irritation SKIN CONTACT: Cause skin irritation

INHALATION: Stomachache, nausea, vomiting INGESTION: Dullness, vision disorder, blindness

CHRONIC TOXICITY / EFFECTS FROM LONG TERM EXPOSURE

SENSITIZATION: Skin sensitizer GERM CELL MUTAGENICITY: No data available CARCINOGENICITY: No data available No data available REPRODUCTIVE TOXICITY:

SPECIFIC TARGET ORGAN SYSTEMIC No data available TOXICITY (SINGLE EXPOSURE)

SPECIFIC TARGET ORGAN SYSTEMIC No data available TOXICITY (REPEATED EXPOSURE)

PRODUCTS NUMERICAL MEASURES OF TOXICITY

NOT DETERMINED

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

SECTION 12: ECOLOGICAL INFORMATION

AQUATIC LIFE: No data available PERSISTENCE AND DEGRADABILITY: No data available BIO ACCUMULATIVE POTENTIAL: No data available MOBILITY IN SOIL: No data available

RESULTS OF PBT AND VPVB ASSESSMENT: No data available as chemical safety assessment not required/not conducted **OTHER ADVERSE EFFECTS:**

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Toxic to aquatic life with long lasting effects.

SAFETY DATA SHEET G-POLY 85 PART B

SECTION 13: DISPOSAL CONSIDERATIONS

WASTE/UNUSED PRODUCTS: Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. This product should not be allowed to enter drains, water courses or the soil Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material. Contact supplier if guidance is required.

CONTAMINATED PACKAGING: Dispose of container and unused contents in accordance with federal, state, and local requirements

SECTION 14: TRANSPORT INFORMATION

Not Dangerous Goods Not Dangerous Goods **Not Dangerous Goods**

SECTION 15: REGULATORY INFORMATION

UNITED STATES

SARA 302 COMPONENTS:

TSCA 8 (B) INVENTORY STATUS: All Components are listed or exempt from listing on the Toxic Substances Control Act Inventory. None above reporting de minimus TSCA 12 (B) EXPORT NOTIFICATION:

> No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

> > ACUTE HEALTH HAZARD:

SARA 313 COMPONENTS: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

SARA 313 COMPONENTS:

CHRONIC HEALTH HAZARD FIRE HAZARD: REACTIVE HAZARD SUDDEN RELEASE OF PRESSURE

CALIFORNIA PROP. 65 COMPONENTS This product may contain chemical known to the State of California to cause birth defects or other reproductive harm.

CEPA DSL/NDSL STATUS All components are listed or exempt from listing on the Domestic Substances List.

SECTION 16: OTHER INFORMATION

NFPA RATING HMIS RATING Health Hazard: Health Hazard: Fire Hazard: Fire Hazard:

Reactivity Hazard: 0 Reactivity Hazard: 0

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and

belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given.